

Snowpack tests for assessing snow-slope instability

Jürg SCHWEIZER¹, J. Bruce JAMIESON^{2,3}

¹ *WSL Institute for Snow and Avalanche Research SLF, Davos, Switzerland
E-mail: schweizer@slf.ch*

² *Department of Civil Engineering, University of Calgary, Calgary AB, Canada*

³ *Department of Geoscience, University of Calgary, Calgary AB, Canada*

ABSTRACT: Information on snowpack instability is crucial for assessing avalanche risk in backcountry operations as well as for operational forecasting of the regional avalanche danger. Since slab avalanche release requires both failure initiation and crack propagation in a weak snowpack layer, field observations should ideally provide reliable information on the probability or propensity of both fracture processes. Even simple field observations that do not require digging a snow pit can provide useful information. Traditional snowpack tests include the shovel shear test, the shear frame test, the compression test (CT) and the rutschblock test (RB). The interpretation of the test results for the CT and RB has been improved by considering the appearance or type of the fracture – in addition to the score. More recently, two tests have been developed that focus on crack propagation rather than initiation: the extended column test (ECT) and the propagation saw test (PST). We compare the sensitivity, specificity and unweighted average accuracy of various stability tests. Comparative studies indicate that the RB, ECT and PST have comparable accuracy. For most test methods the unweighted average accuracy of a single test was 70-90% depending on the dataset. Test methods such as the RB, ECT and PST which fracture an area large enough to include crack propagation, are generally more accurate than test methods that fracture smaller areas (e.g. the CT). The threshold sum method was also less accurate. Even with very experienced observers for RB, ECT and PST an error rate of at least about 5-10% has to be expected. Performing a second, adjacent test on the same slope improves test reliability.

INTRODUCTION

Snow stability data are – as avalanche occurrence data – most closely related to avalanche release probability which is the key parameter to be forecasted by any avalanche forecasting service or backcountry operation. In the context of avalanche forecasting, observations that provide information on snow stability have been termed low entropy data by LaChapelle (1980) or class I data by McClung and Schaerer (2006).

Snow avalanches are – unlike most other mass movements – to a certain degree predictable (Schweizer, 2008). Even more important, in the case of snow avalanches direct observations can be made that provide information on the probability of a mass movement within the next few days. No simple in-situ tests exist to assess, for example, the landslide risk. In that respect, snow stability tests are unique. Subsequently, we will call any test that is made in-situ and that provides information on snowpack instability simply a snow stability test.

These tests are primarily indicators of whether triggering by localized dynamic loading, e.g. people or explosives, is likely. This is appropriate because most fatalities are caused by human triggering (e.g. Schweizer and Lutschg, 2001).

Besides simple field observations on avalanche occurrence, shooting cracks and whumpfs, i.e. sound of collapsing weak layers, that all indicate instability (e.g. Jamieson and others, 2009), a variety of in-situ tests have been developed over the last five decades. All these tests aim to answer the question whether the sloping snowpack is stable or not. None of them provides the definitive answer. The reasons for the insufficiency of the tests are

mainly the inherent limitations of the test (and its loading method) to replicate the avalanche release process, the spatially variable nature of the mountain snowpack (e.g. Schweizer and others, 2008b) and the complexity of the avalanche release process. Repeatedly, the question arose whether the tests are useful at all.

In the following, we will describe test requirements, review the most common existing tests and assess their performance. Test performance will primarily be assessed based on a number of studies that compared various snow stability tests (e.g. Gauthier and Jamieson, 2008b; Moner and others, 2008; Simenhois and Birkeland, 2009; Winkler and Schweizer, 2009).

REQUIREMENTS

It is generally perceived that snow stability tests should answer the question whether a particular slope is stable or unstable. This seems a rather unrealistic aim. First of all, when a test is made on an avalanche slope that slope is assumed stable, otherwise the field team doing the test might have been caught in an avalanche and should not have entered the slope. Consequently, tests are often made on small slopes that do not avalanche or on slopes with a steepness $< 30^\circ$. By doing so, one has to assume that the conditions found on this relatively safe slope are representative of larger and/or steeper slopes of similar aspect in the surroundings. However, due to the spatially variable nature of the snowpack, extrapolation is not straightforward and requires experience. Therefore we suggest that a snow stability test cannot provide the ideal information – that is, whether a slope is stable or not.

For the release of a dry-snow slab avalanche a number of requirements have to be fulfilled. These are: (1) The slope has to have a minimal slope angle ($\sim 30^\circ$). (2) The snow layering has to be such that a cohesive slab layer overlies a weak layer. (3) This slab/weak layer stratigraphy has to exist over a minimal extent of several 10 m^2 . (4) The snowpack has to be in a metastable condition, i.e. the strength of the weak layer is – at least at some locations – of similar magnitude as the applied stress. (5) There is an external (or internal) trigger present. (6) An initial failure tends to propagate. (7) The slab breaks up and slides down-slope (i.e. friction is overcome). The requirements that can be checked are (1), (2), (4) and (6). A trigger (5) inherently exists when applying a stability test. Information on requirement (3) is usually not available, but can occasionally be estimated if the slab/weak layer combination and its formation are known, and (7) is given in most cases on large and steep slopes.

In the context of fractures within weak snowpack layers, we distinguish between failure initiation and crack propagation as in Schweizer and others (2003). A fracture or crack initiates if a localized dynamic perturbation, e.g. a trigger such as a skier, or tapping on the top of a snow column, causes a crack in a weak layer. A crack or fracture that does not advance (propagate) beyond the influence of the localized perturbation is subcritical. A crack or fracture that advances beyond the influence of the localized perturbation has started to propagate. Fractures that were initiated but did not propagate across the slope were documented e.g. by van Herwijnen and Jamieson (2005).

In summary, the snow stratigraphy (slab over weak layer), failure initiation and crack propagation are the most important requirements (apart from steepness) for a dry-snow slab avalanche. A snow stability test needs to provide information whether (or better to which extent) these requirements are fulfilled. In addition, the test should not be difficult to perform, not require special equipment, be completed in less than about 30 minutes and provide robust, repeatable results.

Not much is known about the application of snow stability tests in wet snow, and all results described below refer to dry snow conditions.

SNOW STABILITY TESTS

We will consider two types of observations that provide information on snowpack instability (1) observations that do not require digging (Jamieson and others, 2009), and (2) those that do require digging a snowpit.

The first category includes whumpfs (sudden failure of the weak layer due to rapid, localized loading manifesting itself by collapse), shooting cracks and recent avalanching. These three observations are all unambiguous signs of instability. Further simple observations are, for example, the ski pole test (Tremper, 2008) and cracking at skis.

The second category includes the snow profile and all tests that in one way or the other apply an additional load to the snowpack in order to induce a failure. The latter include the shear frame test (Jamieson and Johnston, 2001; Roch, 1966), the shovel shear test (McClung and Schaerer, 2006), the hand shear test (Tremper, 2008), the rutschblock test (RB) (Föhn, 1987a), the compression test (CT) (Jamieson, 1999), the extended column test (ECT) (Simenhois and Birkeland, 2006) and the propagation saw test (PST) (Gauthier and Jamieson, 2006). The detailed procedures for all these tests are described in Greene and others (2009).

The investigation of snow stratigraphy can be combined/quantified with a structural instability index such as the threshold sum (Schweizer and Jamieson, 2007). In addition, we include the snow micro-penetrometer (SMP) (Schneebeli and Johnson, 1998) in our comparison. It records a penetration resistance-depth profile and can potentially be used to assess snowpack instability (Bellaire and others, 2009).

The shovel (or hand) shear test attempts to shear off the slab above the weak layer, and hence provides an index of shear strength. It is primarily used to find weak layers rather than to assess weak layer strength. However, to properly load the column, the weak layer depth has to be known. The application of the load is delicate and the rating of the load at failure is highly subjective. The shovel shear test has not been validated whereas the hand shear test has been correlated with local avalanche danger (Jamieson and others, 2009) but not with slope scale instability.

The shear frame test is the only in-situ measurement method that measures shear strength. The weak layer to be tested has to be identified by other means such as a snow profile. The slab is removed apart from a few centimetres just above the weak layer. The shear frame test and thereof derived stability indices (Föhn, 1987b) were shown to be related to snowpack instability (Jamieson and Johnston, 1998; Jamieson and others, 2007). Shear frame measurements from study plots are particularly useful to monitor the temporal evolution of snow stability.

The rutschblock test, which can be considered as the grandfather of all snowpack stability tests, involves isolating a snow column of 2 m (cross-slope) \times 1.5 m (up-slope). The block is then loaded in stages by a skier until slab failure. The loading step or score (1 to 7) is noted as well as the release type that is the proportion of the block that released (whole block, most of block, edge only). It has been shown that the RB score is related to the probability of skier-triggered avalanches (Föhn, 1987a; Jamieson, 1995) on the adjacent slope. The RB release type is assumed to be related to crack propagation propensity, in particular since the RB area (3 m²) is – except for deep weak layers – larger than the area for which the skier's load is significant (\sim 1 m²) (Schweizer and Camponovo, 2001). The fact, that Schweizer and others (2008a) found a substantially higher sensitivity for the RB release type (81%) than for the RB score (61%) likely supports this assumption.

With the compression test a much smaller area (30 cm \times 30 cm) is loaded by tapping onto the isolated column. The CT score was shown to be related to the probability of skier-triggered avalanches on adjacent slopes (Jamieson, 1999) and the CT score can be related to the RB score. By introducing the fracture character (van Herwijnen and Jamieson, 2007), the interpretation of the CT was improved and weak layer/slab properties associated with sudden fractures (equivalent to Q1 shear quality as introduced by Johnson and Birkeland (1998)) suggest that the fracture character is related to crack propagation propensity.



Fig. 1: Rutschblock test (photo: J. Schweizer/SLF).

A number of other small column tests have been developed that all aim at replacing the subjective tapping onto the isolated column by a more quantitative loading procedure. Among those are the rammrutsch (or drop hammer test) (Schweizer and others, 1995; Stewart and Jamieson, 2002), the stuffblock test (Birkeland and Johnson, 1999), and the quantified loaded column test (Landry and others, 2001). Since these are variations of the compression test and most have limited validation data, we do not include them in our analysis.



Fig. 2: Compression test (photo: C. Fierz/SLF).

The recently developed extended column test (ECT) was introduced as a test that should provide information on fracture initiation and propagation (Simenhois and Birkeland, 2006). The ECT involves isolating a column of 30 cm × 90 cm (with the longer side cross-slope) and loading it in one corner the same way as with the CT. It is noted primarily whether a fracture crosses the entire column. Simenhois and Birkeland (2009) showed that the ECT is highly indicative of snowpack instability on nearby slopes.



Fig. 3: Extended column test (photo: C. Mitterert/SLF).

The propagation saw test (PST) was inspired by traditional beam-type tests. It is a fracture mechanical test, in which the resistance of a material to fracture in the presence of a crack is tested. In a fracture mechanical test, either the sample is loaded until failure for a given crack length, or the crack length is continuously increased (under constant load) until failure occurs. Sigrist and Schweizer (2007) and Gauthier and Jamieson (2006) were the first



Fig. 4: Propagation saw test (photo: J. Schweizer/SLF).

to report on a suitable design for a field test. A snow column (30 cm × ~100 cm) is isolated with the longer side up-slope. The length should be at least 100 cm or the slab thickness whichever is longer. After the weak layer is identified by a separate test such as the CT or profile, a cut is made along the weak layer with a snow saw until the crack length becomes critical and self propagation of the crack starts. The critical crack length is noted and whether the crack propagates to the end of the column or not. As the free surface influences crack propagation, McClung (personal communication, 2009) suggested not isolating the column at its up-slope end. Gauthier and Jamieson (2008a) validated the PST and showed that at sites where weak layer failure initiation was confirmed on adjacent slopes, PST results were clearly related to observations of crack propagation.

TEST INDICATION

In the following, we rate the above described observations of snowpack instability in regard to the three principal requirements outlined above: (a) Slab/weak layer stratigraphy, (b) failure initiation, (c) crack propagation.

Table 1 compiles the ratings for the simple observations that do not involve digging. Whereas whumpfs, shooting cracks and recent avalanching all indicate that the three requirements are fulfilled, the ski pole test might at best show the existence of a (thick) weak layer, for example, when a cohesionless layer (often consisting of depth hoar) is found below a slab. Cracking at skis only indicates that the surface layer is cohesive, but does not provide information on a possible weak layer.

Table 1: Information in regard to dry-snow slab avalanche formation provided by various observations or tests that do not require digging a snowpit.

Observation/test	Stratigraphy (WL below slab)	Failure initiation	Crack propagation
Whumpfs	yes	yes	yes
Shooting cracks	yes	yes	yes
Recent avalanching	yes	yes	yes
Cracking at skis	partly	no	no
Ski pole test	partly	no	no

Table 2: Information in regard to dry-snow slab avalanche formation provided by various observations or tests that do require digging a snowpit.

Observation/test	Stratigraphy (WL below slab)	Failure initiation	Crack propagation
Snow profile	yes	no	no
Snow profile + Threshold sum	yes	partly	partly
Shear frame test	no	yes	no
Shovel (hand) shear test	partly	yes	no
RB: score + release type	yes	yes	yes
CT: score + fracture character	yes	yes	partly
ECT	yes	yes	yes
PST	no	partly	yes

A snow profile provides snow stratigraphy and shows whether a weak layer below a slab exists (Table 2). Whereas the shear frame test only indicates the strength of the weak layer, the shovel shear test is in addition partly suited for identifying weak layers. For the three tests that involve loading an isolated snow column, the slab/weak layer stratigraphy is shown implicitly when the column fails. In addition, the RB (score and release type) and the ECT both provide information on initiation and propagation. For the CT the information on crack propagation is less well related to crack propagation than for the RB and ECT. Finally, the PST is clearly an index of crack propagation propensity, but does not give any indication on stratigraphy and limited indication on failure initiation. However, digging the pit and sawing might provide some indirect information on stratigraphy.

TEST LIMITATIONS

The use of the tests is influenced by their reliability (see below) and their practicality. Table 3 summarizes some key practical limitations of the tests including the time requirement, required slope angle, effective depth and required technical skill level.

Other than the snow profile, which accompanies most tests, the rutschblock test is the slowest of the tests and the only one to require a sufficiently steep slope. The hand shear test is fast but is limited to weak layers within about 45 cm of the snow surface. The RB, CT, ECT, PST and SMP are all indicative in the 30 to 70 cm range, which is important for skier triggered dry-snow slab avalanches. Ross and Jamieson (2008) report the ECT to be reliable up to about 70 cm in the typically soft snow of the Columbia Mountains of western Canada while Simenhois and Birkeland (2009) report indicative results up to about 100 cm in snow climates with wind-stiffened slab layers. The hand shear, RB, CT, ECT have the advantage of requiring the least skill, whereas the snow profile, shear frame and SMP require the most skill. The SMP is the only test mentioned in this study which requires expensive, electro-mechanical equipment.

Table 3: Key practical limitations of tests including time requirement, required slope angle, effective depth and required technical skill level.

Test	Time (min)	Slope (°)	Depth (cm)	Technical skill
Snow profile	> 30	any	unlimited	high
Shear frame ¹	>15 ³	any	unlimited	high
Shovel shear ¹	10 ³	any	unlimited	moderate
Hand shear	5	any	< 45	low
RB	25 ³	> 25	30-90	low
CT	10 ³	any ⁴	< 100	low
ECT	15 ³	any ⁴	30-70 ⁵	low
PST ¹	15 ³	any ⁴	> 30	moderate
SMP ²	15	any	< 150	high

¹ Difficult for layers which are hard to find in a snow profile.

² Expensive and not used by practitioners.

³ Best done near a snow profile. The time for the snow profile is not included.

⁴ Results are easier to see on steeper slopes.

⁵ Ross and Jamieson (2008). Simenhois and Birkeland (2009) report reliable results down to about 100 cm.

TEST ACCURACY

Early results relating the RB score to the probability of skier-triggered avalanches on nearby slopes have clearly shown that even for high RB scores of 6 or 7 occasionally skier-triggered avalanches were observed (e.g. Jamieson, 1995). These false-stable predictions have shown that snow stability tests are not fool-proof and hence that decisions on where and when to travel in avalanche terrain should never solely rely on stability test results. The false predictions have been attributed to spatial variations of snowpack stability but may also be related to differences between the slab release process and the loading or support in the stability test.

When analysing the performance of snow stability tests observed stability is compared with predicted stability. In most cases only two categories of instability were considered: stable and unstable. For example, rutschblock tests were performed on skier-triggered (unstable) as well as skier-tested (stable) slopes and RB scores < 4 were considered as unstable and ≥ 4 as stable. This type of analysis simplifies the comparison, but oversimplifies the problem. Nevertheless, we will follow this approach and in the following report the test performance by providing the probability of detection (POD, also called sensitivity), the probability of Null events (PON, also called specificity) (Doswell and others, 1990) and their mean, i.e. the unweighted average accuracy (RPC):

$$\text{sensitivity:} \quad \text{POD} = \frac{\text{predicted unstable slopes}}{\text{all observed unstable slopes}} \quad (1)$$

$$\text{specificity:} \quad \text{PON} = \frac{\text{predicted stable slopes}}{\text{all observed stable slopes}} \quad (2)$$

$$\text{unweighted average accuracy:} \quad \text{RPC} = \frac{\text{sensitivity} + \text{specificity}}{2} \quad (3)$$

A test should have both a high sensitivity as well as a high specificity. A high sensitivity means that most unstable situations are detected. If the specificity is high as well then there are only few false alarms. A high sensitivity combined with a low specificity means that the test is oversensitive and produces many false alarms. Whereas false alarms have less severe consequences than misses, a low specificity is not desired since this will promote overcautious decisions which for regional forecasting will lead to a credibility problem in the long run (Williams, 1980). On the other hand, as snow stability tests are commonly used to seek instability rather than stability (McClung, 2002), an unbalanced performance with sensitivity larger than specificity is better than with specificity larger than sensitivity.

To assess the performance of snowpack tests we consider various datasets (Table 4), primarily recent comparative studies. All datasets include a stability test score and an observed stability. The definition of observed stability may vary. For example, in Schweizer and others (2008a) unstable refers to slopes that were skier-triggered. So the tests were made near the perimeter of a skier-triggered avalanche. In most other datasets slopes were rated as unstable if either recent avalanches were observed on adjacent slopes, a whumpf was triggered on the test slope or any other sign of instability was observed. Occasionally, e.g. in the study by Winkler and Schweizer (2009) the slope was also rated as unstable based on an additional criterion, i.e. whether the profile was rated as poor (Schweizer and Wiesinger, 2001). This rating may favour the RB over the other test methods. For most datasets, at least two different snowpack tests were performed on the same test slope, thus they allow comparing the relative performance of the tests (e.g. Moner and other, 2008; Gauthier and Jamieson, 2008b; Simenhois and Birkeland, 2009; Winkler and Schweizer, 2009). For the dataset presented by Schweizer and others (2008a) only rutschblock test

results are available. Dataset A contains test results from slopes where several CTs were performed adjacent to a RB test by University of Calgary avalanche researchers. These so far unpublished data were collected in the Columbia Mountains of western Canada between December 1996 and March 2008. For all datasets, the predicted stability for a given test method is based on a threshold value. Depending on the test score, the test result is either rated as stable or unstable (Table 5).

Table 4: Datasets used to assess test performance. Source, type of snowpack tests performed and the number of test slopes (N) are given. The last column indicates how test slopes were classified as unstable: (1) avalanche on test slope, (2) avalanche on adjacent slope, (3) signs of instability on test slope, (4) profile rated as “Very poor” or “Poor” according to Schweizer and Wiesinger (2001), stability rating “Very poor” or “Poor” (Simenhois and Birkeland, 2009).

Dataset	Source	Tests	N	Observation of instability
A	Unpublished data (see text)	RB, CT	139	1, 3
B	Schweizer and others (2008a)	RB	512	1
C	Winkler and Schweizer (2009)	RB, CT, ECT	146	2, 3, 4
D	Gauthier and Jamieson (2008b)	RB, CT, PST	see Table 6	1
E	Simenhois and Birkeland (2009)	ECT	311	5
E1	Simenhois and Birkeland (2009)	ECT, PST	78	1, 3
F	Moner and others (2008)	RB, ECT	63	1
G	Bellaire and others (2009)	SMP	60	2, 3, 4

Table 5: Critical ranges or thresholds to rate stability test results in regard to stability (stable/unstable).

Test	unstable	stable
RB score	≤ 3	≥ 4
RB release type	whole block release	partial release
CT score	< 14	≥ 14
CT fracture character	sudden planar (SP), sudden collapse (SC)	others
ECT	Fracture crosses entire column within one tap of initiation	others
PST	$< 50\%$ cut length and first propagation reaches the end of the column	$\geq 50\%$ cut length or first propagation stops before the end of the column
Threshold sum	≥ 5	≤ 4

Table 6 compiles the performance measures for the datasets presented in Table 4. As the datasets have distinct properties (e.g. in terms of design and circumstances) and not all test methods were included in each dataset, it is not meaningful to calculate an average performance for a given test method. Instead, one way of assessing the different test methods is to compare their unweighted average accuracy with that of the RB within the same dataset (where the sample size is large or similar) which provides the relative performance (Table 7). To check for differences in the performance of the various tests, the two-proportion Z-test (Spiegel and Stephens, 1999) was used.

Table 6: Performance of various snow stability tests for the datasets described in Table 4. For the threshold sum, the threshold values ≥ 5 and ≥ 4 are considered (the results for the latter one are given in brackets). The base rate gives the proportion of unstable observations.

Test	Data-set	N	Base rate	Sensitivity	Specificity	Unweighted average accuracy
RB: score	A	139	0.54	0.48	0.84	0.66
	B	457	0.44	0.61	0.73	0.67
	C	146	0.25	0.78	0.90	0.84
	D	23	0.70	0.63	0.86	0.74
	F	62	0.44	0.74	0.77	0.76
RB: score <i>and</i> release type	A	33	0.48	0.44	0.71	0.57
	B	185	0.33	0.69	0.85	0.77
	C	146	0.25	0.61	0.99	0.80
	D	23	0.70	0.50	0.86	0.68
	F	29	0.45	0.69	1.0	0.85
RB: score <i>or</i> release type	A	33	0.48	0.88	0.47	0.67
	B	185	0.33	0.89	0.53	0.71
	C	146	0.25	0.94	0.75	0.84
	D	23	0.70	0.75	0.71	0.73
	F	29	0.45	1.00	0.75	0.88
CT: score	A	139	0.54	0.52	0.81	0.67
	C	146	0.25	0.90	0.45	0.68
	D	58	0.71	0.63	0.47	0.55
CT: score <i>and</i> fracture character	A	33	0.48	0.56	0.76	0.66
	C	146	0.25	0.93	0.56	0.75
	D	58	0.71	0.63	0.65	0.64
ECT	C	146	0.25	0.83	0.79	0.81
	E	311	0.40	0.94	0.82	0.88
	E1	78	0.58	1.00	0.91	0.95
	F	47	0.38	0.89	0.97	0.93
PST	D	187	0.60	0.70	0.88	0.79
	E1	78	0.58	0.56	1.00	0.78
Threshold sum ≥ 5 (≥ 4)	B	426	0.50	0.50(0.74)	0.81(0.58)	0.66(0.66)
	C	146	0.25	0.86	0.38	0.62
	D	27	0.63	0.88	0.5	0.69
Snow micro-penetrometer	G	60	0.38	0.78	0.76	0.77

In dataset A, the unweighted average accuracy of RB *or* release type, CT, as well as CT *and* fracture character are within 0.01 of the value for RB; for RB *and* release type the accuracy is 0.09 lower, however, the difference is not statistically significant ($p = 0.36$). In dataset B, the unweighted average accuracy for threshold sum is comparable to that for RB; however, the value for RB *and* release type is significantly higher ($p = 0.01$), while the value for RB *or* release type is 0.04 (not significantly) higher ($p = 0.34$). In dataset C, the accuracy for RB *and* release type is 0.04 lower, for the RB *or* release type and the ECT it is comparable, while the value for the CT is 0.16 lower and for the threshold sum is even lower – only the latter two differences are statistically significant. In dataset D, the unweighted average accuracy for RB *and* release type is 0.06 lower, the value for RB *or* release type is comparable to that of the RB; the value for CT is 0.19 lower and for the threshold sum is 0.05 lower than for RB (while the PST is based on a different sample size). None of the observed differences in unweighted average accuracy in dataset D are statistically significant (due to the partly low sample size). Within dataset E1, the accuracy for ECT is 0.17 (significantly) higher than for PST ($p = 0.002$). Finally, in dataset F, the unweighted average accuracy for ECT is 0.17 (significantly) higher than for RB ($p = 0.01$).

In summary, only for dataset C the sample size is sufficiently large and several tests were included so that a broader comparison is possible. Based on dataset C, the RB and ECT have similar accuracy. On the other hand, dataset E1 suggests that the ECT performs better than the PST, and based on dataset F it seems that the ECT performs better than the RB. Finally, dataset D suggests that the RB and the PST have similar accuracy. Though datasets D, E1 and F are fairly small, the problem of the obviously conflicting conclusions from the various studies cannot be resolved, in particular since none of the studies included all tests and the datasets have partly distinct properties. Based on the available studies and recognizing the differences between datasets, we therefore conclude that the RB, ECT and PST have similar accuracy and that the CT and threshold sum are less accurate. In the following, we report on some of the specific properties of the tests.

If the RB score alone is considered, the rutschblock shows a low false alarm ratio (high specificity) but misses quite a number of unstable situations. The prediction can largely be improved by considering the release type as well (as has been shown by Winkler and Schweizer (2009)). With a RB score ≥ 4 and only a partial release of the block, the conditions are very likely (99%) rather stable, whereas unstable conditions can be expected (94%) if either the RB score is low (< 4) or the whole block released. These findings have been confirmed by Moner and others (2008). In the case of the compression test, considering the fracture character only moderately improves the performance of the CT, which shows a high false alarm ratio, i.e. the CT is oversensitive.

The ECT shows a very balanced performance, and according to Simenhois and Birkeland (2009) has the best unweighted average accuracy of all tests. However, the results from the study by Hendrikx and others (2009) indicate that under some conditions (which cannot be specified yet) the ECT can also be less accurate (about 40%).

The PST does indicate that propagation is unlikely for quite a number of unstable conditions, but shows an unweighted average accuracy of about 80% – comparable to most other tests.

With an unweighted average accuracy of almost 80%, the performance of the SMP is not much lower than the accuracy of the traditional snow stability tests. However, in contrast to most validation studies of the RB, CT, ECT and PST, Bellaire and others (2009) used the same data to establish the instability criterion as for the accuracy.

Given that most studies involved many observers with varying experience under a variety of different conditions and revealed test accuracies of 70-90%, it is apparent that even with a very experienced observer in at least about 5-10% of the cases snow stability will not be predicted correctly by a single stability test.

Table 7: Unweighted average accuracy for the various datasets and test methods. Same data as in Table 6 but compiled with the dataset as main entry to facilitate within dataset comparison. Only datasets which include several test methods are shown.

Dataset	RB: score	RB: score <i>and</i> release type	RB: score <i>or</i> release type	CT: score	CT: score <i>and</i> fracture character	ECT	PST	Threshold sum ≥ 5
A	0.66	0.57	0.67	0.67	0.66	n/a	n/a	n/a
B	0.67	0.77	0.71	n/a	n/a	n/a	n/a	0.66
C	0.84	0.80	0.84	0.68	0.75	0.81	n/a	0.62
D	0.74	0.68	0.73	0.55	0.64	n/a	0.79	0.69
E1	n/a	n/a	n/a	n/a	n/a	0.95	0.78	n/a
F	0.76	0.85	0.88	n/a	n/a	0.93	n/a	n/a

SOURCES OF ERROR

The relatively high number of false predictions undermines the usefulness of snow stability tests. What is causing the false predictions? We propose that there are at least two sources of error. The first is related to the test method itself, the second to the variable nature of the snowpack. Obviously, all test methods are relatively crude methods that involve many subjective elements such as the way of loading. The support or tested area of some tests, such as the CT or shear frame, is too small to capture crack propagation. Any test result will be specific for the test location since the slab as well as weak layer properties may vary within the slope and be different on adjacent slopes. Hence an individual test result may well under or overestimate stability. It is presently not clear what is the contribution of the two sources of error to the overall rate of false predictions. It has been suspected e.g. by Schweizer and others (2008b) that due to test errors, spatial variations of snow stability can not easily be detected, this would mean that the two errors have similar magnitude.

Spatial variability studies that used snow stability tests in conjuncture with the snow micro-penetrometer (SMP) may shed some light on the source of errors. Kronholm (2004) has provided the quartile coefficient of variation (QCV) for the stability test results as well as the weak layer strength penetration resistance. The QCV of the stability test scores was in most cases about 30%, whereas it was only about 20% for the weak layer penetration resistance. As the SMP is considered a high precision instrument that has produced repeatable results, it can be assumed that at least about one third of the observed variation in stability test scores was related to test errors and about two thirds may reflect the real spatial variability of the snowpack. However, it has to be pointed out that the two methods have very different support, 0.09 m^2 (CT) vs. $2 \times 10^{-5} \text{ m}^2$. In fact, one would expect the variation to increase with decreasing support. On the other hand, the variation in stability includes variations of both weak layer and slab properties so that it is expected to be higher than the variation of weak layer penetration resistance. The use of stability tests for spatial variability studies seems somewhat questionable given the obviously significant test error – but so far no alternative exists.

The uncertainty due to test errors can substantially be decreased if two tests adjacent to each other are done. For the case of the rutschblock Jamieson (1995) has shown that the test result is in 97% of the cases within ± 1 score from the slope median – at least on rather uniform slopes. This implies that the probability of the median of two independent tests being within one half or one step of the slope median score is 0.91 or 0.99, respectively.

Winkler and Schweizer (2009) found that with two adjacent ECT's which provide the same test result, the unweighted average accuracy increased from about 80% to about 90%. Birkeland and Chabot (2006) proposed that the false-stable error rate could be reduced from about 10% to about 1% by making a second test at a representative site beyond the correlation length from the first test and choosing the least stable of the two test results. As the correlation length is unknown, at least about 10 m have been proposed as the distance between two tests (Jamieson and Johnston, 1993; Schweizer and others, 2008b).

CONCLUSIONS

Snow stability tests represent highly prized class I data. They can be considered as indices of instability. They represent the only way to get information on (1) layering, (2) failure initiation and (3) crack propagation (in the absence of obvious signs of instability). Despite obvious deficiencies, they are useful for assessing avalanche risk in backcountry operations as well as for operational forecasting of the regional avalanche danger, in particular in areas with persistent weak snowpack layers.

A good test method should predict stable and unstable conditions similarly well (sensitivity vs. specificity). Combinations of test results (from the same or different methods) are useful, as exemplified by rutschblock scores and release type. Comparisons *across* datasets require cautious interpretation. Nevertheless, with this approach, the ECT has generally higher unweighted average accuracy than other tests. On the other hand, comparisons *within* datasets suggest that ECT, RB, PST (and the SMP) generally have a comparable accuracy – but higher than the CT. This is likely because the areas of the weak layer tested by the ECT, RB and PST are large enough to represent crack propagation, whereas the CT tests for failure initiation in about 0.09 m² of the weak layer, and hence has low specificity. The threshold sum provides no direct information about failure initiation or propagation and has a lower unweighted average accuracy than any of the tests which fracture weak layers. This is consistent with LaChapelle (1980) who stated that observations of snowpack mechanics were more directly related to avalanching than observations of stratigraphy.

Even with very experienced observers an error rate of at least about 5-10% has to be expected. Site selection and interpretation requires experience. Stability test are not fool-proof. And, decisions about travelling in avalanche terrain should not solely be based on stability test results. Obviously, test reliability increases when two adjacent tests are done. However, a second test on a different slope (or at a second site on the same slope which is more than the autocorrelation length from the first site), should be more useful than the same test repeated in the same snow pit.

While accuracy is relevant when selecting a test for various scales of forecasting or backcountry decisions, considerations such as the effective depth, required time and technical skill are also important.

ACKNOWLEDGEMENTS

We thank Ivan Moner and Dave Gauthier for providing additional information on their datasets, and Alec van Herwijnen for valuable suggestions on the manuscript. For financial and logistical support, B.J. is grateful to Canada's Natural Sciences and Engineering Council of Canada, HeliCat Canada, Canadian Avalanche Association, Canada West Ski Areas Association, Mike Wiegele Helicopter Skiing, Backcountry Lodges of British Columbia, Association of Canadian Mountain Guides, Parks Canada, Canadian Ski Guide Association, and Teck Mining Company. J.S. acknowledges support by the European Commission under contract NEST-506 2005-PATH-COM-043386 (TRIGS). Thorough review comments helped to improve this paper.

REFERENCES

- Bellaire, S., C. Pielmeier, M. Schneebeli and J. Schweizer. 2009. Stability algorithm for snow micro-penetrometer measurements. *J. Glaciol.*, **55**(193), 805-813.
- Birkeland, K.W. and R.F. Johnson. 1999. The stuffblock snow stability test: comparability with the rutschblock, usefulness in different snow climates, and repeatability between observers. *Cold Reg. Sci. Technol.*, **30**(1-3), 115-123.
- Birkeland, K.W. and D. Chabot. 2006. Minimizing "false stable" stability test results: Why digging more snowpits is a good idea. *In* J.A. Gleason *ed.*, Proceedings ISSW 2006. International Snow Science Workshop, Telluride CO, U.S.A., 1-6 October 2006, 498-504.
- Doswell, C.A., R. Davie-Jones and D.L. Keller. 1990. On summary measures of skill in rare event forecasting based on contingency-tables. *Weather and Forecasting*, **5**(4), 576-585.
- Föhn, P.M.B. 1987a. The Rutschblock as a practical tool for slope stability evaluation. *In* B. Salm and H. Gubler *eds.*, Symposium at Davos 1986 - Avalanche Formation, Movement and Effects, IAHS Publ., 162. International Association of Hydrological Sciences, Wallingford, Oxfordshire, U.K., 223-228.
- Föhn, P.M.B. 1987b. The stability index and various triggering mechanisms. *In* B. Salm and H. Gubler *eds.*, Symposium at Davos 1986 - Avalanche Formation, Movement and Effects, IAHS Publ., 162. International Association of Hydrological Sciences, Wallingford, Oxfordshire, U.K., 195-214.
- Gauthier, D. and J.B. Jamieson. 2006. Towards a field test for fracture propagation propensity in weak snowpack layers. *J. Glaciol.*, **52**(176), 164-168.
- Gauthier, D. and B. Jamieson. 2008a. Fracture propagation propensity in relation to snow slab avalanche release: Validating the Propagation Saw Test. *Geophys. Res. Lett.*, **35**(13), L13501.
- Gauthier, D. and J.B. Jamieson. 2008b. Predictions of the propagation saw test: comparisons with other instability tests at skier tested slopes. *In* C. Campbell, S. Conger and P. Haegeli *eds.*, Proceedings ISSW 2008, International Snow Science Workshop, Whistler, Canada, 21-27 September 2008, 408-414.
- Greene, E., D. Atkins, K.W. Birkeland, K. Elder, C. Landry, B. Lazar, I. McCammon, M. Moore, D. Sharaf, C. Sterbenz, B. Tremper and K. Williams. 2009. Snow, weather, and avalanches: Observational guidelines for avalanche programs in the United States. 2nd ed. American Avalanche Association, Pagosa Springs CO, U.S.A.
- Jamieson, B., P. Haegeli and J. Schweizer. 2009. Field observations for estimating the local avalanche danger in the Columbia Mountains of Canada. *Cold Reg. Sci. Technol.*, **58**(1-2), 84-91.
- Jamieson, J.B. 1995. Avalanche prediction for persistent snow slabs. (Ph.D. thesis, University of Calgary.)
- Jamieson, J.B. 1999. The compression test - after 25 years. *The Avalanche Review*, **18**(1), 10-12.
- Jamieson, J.B. and C.D. Johnston. 1993. Experience with rutschblocks. Proceedings International Snow Science Workshop, Breckenridge, Colorado, U.S.A., 4-8 October 1992, Colorado Avalanche Information Center, Denver CO, USA, 150-159.
- Jamieson, J.B. and C.D. Johnston. 1998. Refinements to the stability index for skier-triggered dry slab avalanches. *Ann. Glaciol.*, **26**, 296-302.
- Jamieson, J.B. and C.D. Johnston. 2001. Evaluation of the shear frame test for weak snowpack layers. *Ann. Glaciol.*, **32**, 59-68.
- Jamieson, J.B., A. Zeidler and C. Brown. 2007. Explanation and limitations of study plot stability indices for forecasting dry snow slab avalanches in surrounding terrain. *Cold Reg. Sci. Technol.*, **50**(1-3), 23-34.

- Johnson, R. and K. Birkeland. 1998. Effectively using and interpreting stability tests. Proceedings International Snow Science Workshop, Sunriver, Oregon, U.S.A., 27 September-1 October 1998. Washington State Department of Transportation, Olympia WA, USA, 562-565.
- Hendrikx, J., K. Birkeland and M. Clark. 2009. Assessing changes in the spatial variability of the snowpack fracture propagation propensity over time. *Cold Reg. Sci. Technol.*, **56**(2-3), 152-160.
- Kronholm, K. 2004. Spatial variability of snow mechanical properties with regard to avalanche formation. (Ph.D. thesis, University of Zurich.)
- LaChapelle, E.R. 1980. The fundamental process in conventional avalanche forecasting. *J. Glaciol.*, **26**(94), 75-84.
- Landry, C.C., J.J. Borkowski and R.L. Brown. 2001. Quantified loaded column stability test: mechanics, procedure, sample-size selection, and trials. *Cold Reg. Sci. Technol.*, **33**(2-3), 103-121.
- McCammon, I. and Sharaf, D., 2005. Integrating strength, energy and structure into stability decisions: So you dig a pit and then what? *Avalanche Rev.*, **23**(3): 18-19.
- McClung, D.M. 2002. The elements of applied forecasting - Part I: The human issues. *Nat. Hazards*, **26**(2), 111-129.
- McClung, D.M. and P. Schaerer. 2006. The Avalanche Handbook, 3rd ed. The Mountaineers Books, Seattle WA, U.S.A.
- Moner, I., J. Gavalda, M. Bacardit, C. Garcia and G. Martí. 2008. Application of the field stability evaluation methods to the snow conditions of the Eastern Pyrenees. In C. Campbell, S. Conger and P. Haegeli eds., Proceedings ISSW 2008, International Snow Science Workshop, Whistler, Canada, 21-27 September 2008, 386-392.
- Roch, A. 1966. Les variations de la résistance de la neige, Symposium at Davos 1965 - Scientific Aspects of Snow and Ice Avalanches, IAHS Publ., 69. International Association of Hydrological Sciences, Wallingford, Oxfordshire, U.K., 86-99.
- Ross, C. and B. Jamieson. 2008. Comparing fracture propagation tests and relating test results to snowpack characteristics In C. Campbell, S. Conger and P. Haegeli eds., Proceedings ISSW 2008, International Snow Science Workshop, Whistler, Canada, 21-27 September 2008, 376-385.
- Schneebeli, M. and J.B. Johnson. 1998. A constant-speed penetrometer for high-resolution snow stratigraphy. *Ann. Glaciol.*, **26**, 107-111.
- Schweizer, J. 2008. On the predictability of snow avalanches. In C. Campbell, S. Conger and P. Haegeli eds., Proceedings ISSW 2008, International Snow Science Workshop, Whistler, Canada, 21-27 September 2008, 688-692.
- Schweizer, J. and C. Camponovo. 2001. The skier's zone of influence in triggering slab avalanches. *Ann. Glaciol.*, **32**, 314-320.
- Schweizer, J. and M. Lutschg. 2001. Characteristics of human-triggered avalanches. *Cold Reg. Sci. Technol.*, **33**(2-3), 147-162.
- Schweizer, J. and J.B. Jamieson. 2007. A threshold sum approach to stability evaluation of manual snow profiles. *Cold Reg. Sci. Technol.*, **47**(1-2), 50-59.
- Schweizer, J., M. Schneebeli, C. Fierz and P.M.B. Föhn. 1995. Snow mechanics and avalanche formation: Field experiments on the dynamic response of the snow cover. *Surveys in Geophysics*, **16**(5-6), 621-633.
- Schweizer, J., I. McCammon and J.B. Jamieson. 2008a. Snowpack observations and fracture concepts for skier-triggering of dry-snow slab avalanches. *Cold Reg. Sci. Technol.*, **51**(2-3), 112-121.

- Schweizer, J., K. Kronholm, J.B. Jamieson and K.W. Birkeland. 2008b. Review of spatial variability of snowpack properties and its importance for avalanche formation. *Cold Reg. Sci. Technol.*, **51**(2-3), 253-272.
- Schweizer, J. and T. Wiesinger. 2001. Snow profile interpretation for stability evaluation. *Cold Reg. Sci. Technol.*, **33**(2-3), 179-188.
- Sigrist, C. and J. Schweizer. 2007. Critical energy release rates of weak snowpack layers determined in field experiments. *Geophys. Res. Lett.*, **34**(3), L03502.
- Simenhois, R. and K.W. Birkeland. 2006. The extended column test: a field test for fracture initiation and propagation. *In* J.A. Gleason *ed.*, Proceedings ISSW 2006. International Snow Science Workshop, Telluride CO, U.S.A., 1-6 October 2006, 79-85.
- Simenhois, R. and K.W. Birkeland. 2009. The extended column test: Test effectiveness, spatial variability, and comparison with the propagation saw test. *Cold Reg. Sci. Technol.*, **59**(2-3), 210-216.
- Spiegel, M.R. and L.J. Stephens. 1999. Schaum's outline of theory and problems of statistics. Schaum's outline series. McGraw-Hill, New York, 538 pp.
- Stewart, K. and J.B. Jamieson. 2002. Spatial variability of slab stability in avalanche start zones. *In* J.R. Stevens *ed.*, Proceedings ISSW 2002, International Snow Science Workshop, Penticton BC, Canada, 29 September-4 October 2002, 544-548.
- Tremper, B., 2008. Staying alive in avalanche terrain. 2nd. ed. The Mountaineers Books, Seattle, U.S.A., 318 pp.
- van Herwijnen, A.F.G. and J.B. Jamieson. 2005. High-speed photography of fractures in weak snowpack layers. *Cold Reg. Sci. Technol.*, **43**(1-2), 71-82.
- van Herwijnen, A. and J.B. Jamieson. 2007. Fracture character in compression tests. *Cold Reg. Sci. Technol.*, **47**(1-2), 60-68.
- Williams, K. 1980. Credibility of avalanche warnings. *J. Glaciol.*, **26**(94), 93-96.
- Winkler, K. and J. Schweizer. 2009. Comparison of snow stability tests: Extended column test, rutschblock test and compression test. *Cold Reg. Sci. Technol.*, **59**(2-3), 217-226.